

Page 1 of 7

CND-N-004

MSDS Revision Date 11/01/2002

		1. F	RODUC	[IDENTI	FICATIO	N			
1.1	Product Name:								
	COOL BLUE								
1.2	Chemical Name: ETHANOL SOLUTION								
1.3	Synonyms: ETHYL ALCOHOL SOLUTION								
1.4	Trade Names:								
1.5	Product Use: COSMETIC USE ONLY								
1.6	Manufacturer's Name: CREATIVE NAIL DESIGN, INC.								
1.7	Manufacturer's Address: 1125 JOSHUA WAY, VISTA, CA 9	2083							
1.8	Emergency Phone:	2000							
	ROCKY MOUNTAIN POISO	N CONTROL (CENTER:	1-303	3-623-571	6			
1.9	Business Phone:								
	1-800-833-NAIL (6245)								
	2	COMPOSI	TION 0 I	NCBEDI	ENIT INIE/) N		
		COMPOSI	IION & I	NGKEDI	EINT HALC			415	
			}	۸۲	GIH	EXPOSURE LIMITS IN AIR OSHA			OTHER
			<u> </u>	TLV	STEL	PEL	STEL	IDLH	OTHER
	CHEMICAL NAME(S)	CAS NO.	%	ppm	ppm	ppm	ppm	ppm	
ETHAI	NOL	64-17-5	> 80.0	1000	NE	1000	NE	NE	
WATE	R	7732-18-5		NE	NE	NE	NE	NE	
	ROPANOL	67-63-0		400	NE	400	NE	NE	
	RANCE	NA		NE NE	NE NE	NE NE	NE NE	NE NE	
	OXYETHYL CELLULOSE R COMPONENTS PRESENT IN LESS	9004-62-0	BALANCE						NY SIGNIFICANT
	1% CONCENTRATION		BALANCE	ITIL KLIVIA	AIINING CON		NAL HAZAR		NI SIGNIFICANI
			+ +						
NA =	Not Available; ND = Not Determ	ined; NE = Not Es	tablished; C	= Ceiling Li	mit; See Sec	tion 16 for A	dditional [Definitions (of Terms Used

NOTE: all WHMIS required information is included. It is located in appropriate sections based on the ANSI Z400.1-1998 format.



Page 2 of 7

CND-N-004

Pre	oared to OS	HA, ACC, ANSI and WHM	IS Standards			MSDS	Revisio	n Date 11/0	01/2002
		3	B. HAZARD I	DENTIE	CATION				
3.1	Hazard Identificati		O. HAZAKU I	DEINIII	CAHON				
3.2	Routes of Entry:	Inh	nalation:	YES	Absorption:	YES	Ingest	ion:	YES
3.3	Effects of Exposure: INGESTION: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system depression. SKIN & EYES: Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. May be irritating to skin, especially after prolonged contact. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure.								
	INHALATION: Vapors of this product may be moderately irritating to the nose, throat and other tissues of the respiratory system Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing. Inhalation concentrated vapors can cause central nervous system depression (e.g., drowsiness, dizziness, headaches, nausea).							alation of	
3.4	Symptoms of Overexposure: Symptoms of skin overexposure may include redness, itching, and irritation of affected areas. Overexposure in eyes may cause redness, itching and watering. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure.								
3.5	Acute Health Effects: Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.								
3.6	Chronic Health Effects: None known								
3.7	Target Organs: Eyes, skin & respiratory system.								
			4. FIRST A	ID MEA	SIIRES				
4.1	First Aid:		4. IIKSI A	ID MILA	JUKES				
	INGESTION: If ingested, do not induce vomiting! If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact Rock Mountain Poison Control Center at 1-303-623-5716 or the nearest Poison Control Center or local emergency number Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed. SKIN: If irritation occurs & product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with plenty of soap and water. Remove contaminated clothing and wash thoroughly before reuse. irritation, redness or swelling persists, consult a physician immediately.					number.			
						•			
	EYES:	If product gets in the eyes, fl eyelid(s) while flushing to ensu	•						ınd lower
	INHALATION:	Remove victim to fresh air at a	once. If breathing	stops, per	form artificial res	piration. See	k immed	iate medical d	attention.
4.2	Medical Conditions Aggravated by Exposure: Pre-existing dermatitis, other skin conditions, and disorders of the target organs (eyes,					HEALTH	1		
	skin, respiratory system).			me raigei oigans (eyes,	FLAMMABILITY			3	
						REACTIV	ITY		1
						PROTECT	IVE EG	QUIPMENT	Α
						EYES			



Page 3 of 7

CND-N-004

Prepared to OSHA, ACC, ANSI and WHMIS Standards

MSDS Revision Date 11/01/2002

5. FIREFIGHTING MEASURES

NE

5.1 Flashpoint & Method:

28°C (83°F)
5.2 Autoignition Temperature:

ND

5.4

IND

5.3 Flammability Limits:

This product is a flammable liquid. When involved in a fire, this product may ignite and decompose to form toxic gases (e.g., CO, CO2, NOx).

5.5 Extinguishing Methods

Water, Foam, CO₂, Dry Chemical

5.6 Firefighting Procedures:

First responders should wear eye protection. For spills > 1 gallon, evacuate and deny entry to all individuals. Structural fire fighters must wear full protective equipment and MSHA/NIOSH-approved self-contained breathing apparatus. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas. If necessary, rinse contaminated equipment with soapy water before returning to service.



Upper Explosive Limit (UEL):

RED = FLAMMABILITY
BLUE = HEALTH
YELLOW = REACTIVITY
WHITE = SPECIAL MEASURES

NE

0 = NO HAZARD 1 = MINIMAL HAZARD 2= SLIGHT HAZARD 3 = MODERATE HAZARD 4 = SEVERE HAZARD

6. ACCIDENTAL RELEASE MEASURES

6.1 Spills:

Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment.

Lower Explosive Limit (LEL):

For small spills (e.g., <1 gallon) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse.

For spills ≥ 1 gallon, deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

7. HANDLING & STORAGE INFORMATION

7.1 Work & Hygiene Practices:

Avoid prolonged contact with this material. Avoid breathing the vapors generated by this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). If necessary, use a moisturizer after washing. Do not eat, drink, or smoke while handling this product.

7.2 Storage & Handling:

Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans). Keep away from excessive heat, open flames, sparks, and other possible sources of ignition. Keep away from incompatible materials listed in Section 10. Do not store in damaged or unmarked containers or storage devices. Keep containers securely closed when not in use. Open slowly on a level, stable surface. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care. As a precaution against exposure to the eyes, nose, throat and face, this product should not be stored higher than waist level. Keep away from children at all times!

7.3 Special Precautions:

None.

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1 Ventilation & Engineering Controls:

Use with adequate ventilation (e.g., open doors and windows, local exhaust ventilation). Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station).

8.2 Respiratory Protection:

No special respiratory protection is required under typical circumstances of use or handling. In instances where vapors or sprays of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia.

8.3 Eye Protection:

Safety glasses with side shields should be used with this product. Always use protective eyewear when cleaning spills or leaks.



Page 4 of 7

CND-N-004

Prepared to OSHA, ACC, ANSI and WHMIS Standards

MSDS Revision Date 11/01/2002

8.4 Hand Protection:

None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals.

When handling large quantities (e.g., ≥ 1 gallon), wear rubber or plastic impervious gloves.

8.5 Body Protection

No apron required when handling small quantities.

When handling large quantities (e.g., ≥ 1 gallon),—eye wash stations and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water.

		9. PHYSICAL & CHEMICAL PROPERTIES			
9.1	Density:	~0.9 (water=1)			
9.2	Boiling Point:				
9.3	Melting Point:	ND NE			
9.4	Evaporation Rate:	NE N			
	· ·	>1 (n-BuAc=1)			
9.5	Vapor Pressure:	ND			
9.6	Molecular Weight:	NE .			
9.7	Appearance & Color:	Pale blue gel with a citrusy odor.			
9.8	Odor Threshold:	NE			
9.9	Solubility:	Soluble.			
9.10	рН	NA NA			
9.11	Viscosity:	NE NE			
9.12	Other Information:	Vapor density (air=1): > 1			
		10. STABILITY & REACTIVITY			
10.1	Stability:	Relatively stable under ambient conditions when stored properly.			
10.2	Hazardous Decomposition Products:	If exposed to <u>extremely high temperatures</u> , products of thermal decomposition may include irritating vapors and toxic gases (e.g., oxides of carbon & nitrogen).			
10.3	Hazardous Polymerization:	Will not occur.			
10.4	Conditions to Avoid:	Exposure or contact to extreme temperatures, incompatible chemicals, strong light sources, sparks flame.			
10.5	Incompatible Substances:	Strong oxidizers, peroxides or strong acids.			
		onong oxidizers, peroxides or shoring delicas.			
		11. TOXICOLOGICAL INFORMATION			
11.1	Toxicity Data:	This product has not been tested on animals to obtain toxicological data. There are toxicology data for the components of this product, which are found in the scientific literature. These data have no been presented in this document.			
11.2	Acute Toxicity:	See Section 3.5			
11.3	Chronic Toxicity:	See Section 3.6			
11.4	Suspected Carcinogen:	NE			
11.5	Reproductive Toxicity:	112			
11.5	Mutagenicity:	None			
	Mulagericity.	NO. However, animal mutation data are available for the components of this product that were obtained during clinical studies on specific animal tissues exposed to high doses of these components.			
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.			
	Teratogenicity:	This product is not reported to cause teratogenic effects in humans.			
	Reproductive Toxicity:	This product is not reported to cause reproductive effects in humans.			
11.6	Irritancy of Product:	See Section 3.3			
	Diele eigel Franze von Inglieden				
11.7	Biological Exposure Indices:	l NE			



Page 5 of 7

CND-N-004

Prepared to OSHA, ACC, ANSI and WHMIS Standards MSDS Revision Date 11/01/2002 12. ECOLOGICAL INFORMATION Environmental Stability: This product will slowly volatile from soil. Components of this product will slowly decompose into organic compounds. Effects on Plants & Animals: 12.2 There is no specific data available for this product. 12.3 Effects on Aquatic Life: There is no specific data available for this product. Releases of large volumes may be harmful or fatal to overexposed aquatic life. Aquatic toxicity data for components of this product are available, but are not presented in this MSDS. 13. DISPOSAL CONSIDERATIONS 13 1 Waste Disposal: Dispose of in accordance with federal, state or local regulations. 13.2 Special Considerations: U.S. EPA Characteristic Waste: D001 (flammable) 14. TRANSPORTATION INFORMATION The basic description (proper shipping name, hazard class & division, ID Number, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND): CONSUMER COMMODITY CONSUMER COMMODITY, ORM-D ($\leq 5.0 \text{ L}$) 14.2 IATA (AIR): ORM-D CONSUMER COMMODITY, ORM-D (≤ 5.0 L) 14.3 IMDG (OCN): FLAMMABLE LIQUIDS, N.O.S. (ethanol, isopropanol), 3, UN1993, III, LTD QTY (≤ 5.0 L) 14.4 TDGR (Canadian GND): MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 5.0 L) 15. REGULATORY INFORMATION SARA Reporting Requirements: 15.1 SARA 313 (Isopropanol) 15.2 SARA Threshold Planning Quantity: Not applicable. 15.3 TSCA Inventory Status: All components of this product are listed in the TSCA Inventory or are exempt. 15.4 CERCLA Reportable Quantity (RQ): Not applicable. Other Federal Requirements: 15.5 This product has been classified according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. Class C1 Flammable Liquid. State Regulatory Information: Ethanol is covered under specific state criteria. Ethanol, a component of this mixture is listed in the California Proposition 65 Lists (alcoholic beverages only).



Page 6 of 7

CND-N-004

Prepared to OSHA, ACC, ANSI and WHMIS Standards

MSDS Revision Date 11/01/2002

16. OTHER INFORMATION

16.1 Other Information:

FLAMMABLE! Keep away from heat or flame. Use only as directed. Do not ingest. If swallowed, do not induce vomiting; seek medical attention. Avoid eye contact. Keep out of reach of children.

16.2 Terms & Definitions:

See page 7 of this MSDS.

16.3 Disclaimer:

This Material Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Creative Nail Design's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

16.4 Prepared for

Creative Nail Design, Inc.
1125 Joshua Way
Vista, CA 92083
1-800-833-NAIL (6245) phone
760-599-4005 fax
http://www.creativenaildesign.com/



16.5 Prepared by: ShipMate, Inc. 18436 Hawthorne Boulevard, Suite 201 Torrance, CA 90504 310-370-3600 phone







Page 7 of 7

CND-N-004

Prepared to OSHA, ACC, ANSI and WHMIS Standards

MSDS Revision Date 11/01/2002

DEFINITIONS OF TERMS

A large number of abbreviations and acronyms appear on a MSDS. Some of these which are commonly used include the following:

CAS #: This is the Chemical Abstract Service Number that uniquely identifies each constituent.

EXPOSURE LIMITS IN AIR:

ACGIH - The American Conference on Governmental Industrial Hygienists, a professional association that establishes exposure limits.

TLV – Threshold Limit Value – an airborne concentration of a substance that represents conditions under which it is generally believed that all workers may be repeatedly exposed without adverse effect. The duration must be considered, including the 8-hour Time Weighted Average (TWA), the 15-minute Short Term Exposure Limit, and the instantaneous Ceiling Level (C). Skin absorption effect must also be considered.

OSHA – U.S. Occupational Safety and Health Administration

PEL – Permissible Exposure Limit – This exposure value means exactly the same as TLV, except that it is enforceable by OSHA. The OSHA Permissible Exposure Limits are based in the 1989 PELs and the June 1993 Air Contaminants Rule (Federal Register: 58: 35338-35351 and 58: 40191). Both the current PELs and the vacated PELs are indicated. The phrase "Vacated 1989 PEL," is placed next to the PEL which was vacated by Court Order.

IDLH – Immediately Dangerous to Life and Health – This level represents a concentration from which one can escape within 30-minutes without suffering escape-preventing or permanent injury. The **DFG** – **MAK** is the Republic of Germany's Maximum Exposure Level, similar to the U.S. PEL. NIOSH is the National Institute of Occupational Safety and Health, which is the research arm of the U.S. Occupational Safety and Health Administration (**OSHA**). NIOSH issues exposure guidelines called Recommended Exposure Levels (**RELs**) When no exposure guidelines are established, an entry of **NE** is made for reference.\

FIRST AID MEASURES:

CPR: Cardiopulmonary resuscitation. Method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.

HAZARD RATINGS:

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: This rating system was developed by the National Paint and Coating Association and has been adopted by industry to identify the degree of chemical hazards. Health Hazard: 0 (minimal acute or chronic exposure hazard); 1 (slight acute or chronic exposure hazard); 2 (moderate acute or significant chronic exposure hazard); 3 (severe acute exposure hazard; onetime overexposure can result in permanent injury and may be fatal); 4 (extreme acute exposure hazard; onetime overexposure can be fatal). Flammability hazard: 0 (minimal hazard); 1 (materials that require substantial pre-heating before burning; 2 (combustible liquids or solids; liquids with a flashpoint of 38-93C [100-200F]); 3 (Class 1B and 1C flammable liquids with flash points below 38C [100F]; 4 (Class 1A flammable liquids with flash points below 23C [73F] and boiling points below 38C [100F]. Reactivity Hazard: 0 (normally stable); 1 (materials that can become unstable at elevated temperatures or which can react slightly with water); 2 (materials that are unstable but do not detonate when initiated or which can react violently with water); 3 (materials that can detonate when initiated or which can react explosively with water); 4 (materials that can detonate at normal temperatures or pressures). PPE Rating X: An industrial hygienist should specify personal protective equipment.

NATIONAL FIRE PROTECTION ASSOCIATION: Health Hazard: 0 (material that on exposure under fire conditions would offer no hazard beyond that of ordinary combustible materials); 1 (materials that on exposure under fire conditions could cause irritation or minor residual injury); 2 (materials that on intense or continued exposure under fire conditions could cause temporary incapacitation or possible residual injury); 3 (materials that can on short exposure could cause serious temporary or residual injury); 4 (material that under very short exposure could cause death or major residual injury). Flammability Hazard and Reactivity Hazard: Refer to definitions for

"Hazardous Materials Identification System."

FLAMMABILITY LIMITS IN AIR:

Much of the information related to fire and explosion is derived from the National Fire Protection Association (NFPA). Flash Point – minimum temperature at which a liquid gives off sufficient vapors to form an ignitable mixture with air. Autoignition Temperature: The minimum temperature required to initiate combustion in air with no other source of ignition. LEL – the lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source. UEL – the highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source.

TOXICOLOGICAL INFORMATION:

Human and Animal Toxicology: Possible health hazards as derived from human data, animal studies, or from the results of studies with similar compounds are presented. Definitions of some terms use dint his section are: LD₅₀ – Lethal Dose (solids & liquids) which kills 50% of the exposed animals; LC₅₀ – Lethal concentration (gases) which kills 50% of the exposed animals; ppm – concentration expressed in parts of material per million parts of air or water; mg/m^3 - concentration expressed in weight of substance per volume of air; mg/kg quantity of material, by weight, administered to a test subject, based on their body weight in kg. Other measures of toxicity include TDLo, the lowest dose to cause a symptom and **TCLo** the lowest concentration to cause a symptom; TDO, LDLo, and LDo, or TC, TCo, LCLo, and LCo, the lowest dose (or concentration) to cause lethal or toxic effects. Cancer Information: The sources are: IARC - the International Agency for Research on Cancer; NTP - the National Toxicology Program, RTECS - the Registry of Toxic Effects of Chemical Substances, OSHA and CAL/OSHA. IARC and NTP rate chemicals on a scale of decreasing potential to cause human cancer with rankings from 1 to 4. Subrankings (2A, 2B, etc.) are also used. Other Information: BEI - ACGIH Biological Exposure Indices, represent the levels of determinants which are most likely to be observed in specimens collected from a health worker who has been exposed to chemical to the same extent as a worker with inhalation exposure to the TLV. **Ecological Information**: EC is the effect concentration in water. BCF - Bioconcentration Factor, which is used to determine if a substance will concentrate in life forms that consume contaminated plant or animal matter. TL_m - median threshold limit; Coefficient of Oil/Water Distribution is represented by log Kow or log Koc and is used to assess a substance's behavior in the environment.

REGULATORY INFORMATION:

U.S. and CANADA: This section explains the impact of various laws and regulation of the material. **EPA** is the U.S. Environmental Protection Agency. **WHMIS** is the Canadian Workplace Hazardous Material Information System. **DOT** and **TC** and the U.S. Department of Transportation and the Transport Canada, respectively. Superfund Amendments and Reauthorization Act (**SARA**); the Canadian Domestic/Non-Domestic Substance List (**DSL/NDSL**); the U.S. Toxic Substance Control Act (**TSCA**); Marine Pollutant status according to the DOT; the Comprehensive Environmental Response, Compensation, and Liability Act (**CERCLA or Superfund**); and various state regulations. This section also includes information on the precautionary warnings that appear on the material's package label.

EUROPEAN and INTERNATIONAL: EC is the European Community, formerly known as the EEC, European Economic Community). **EINECS:** This is the European Inventory of Now-Existing Chemical Substances. **AICS** is the Australian Inventory of Chemical Substances. **MITI** is the Japanese Minister of International Trade and Industry. **ECL** is the Korean Existing Chemicals List. **IMO** is the International Maritime Organization and **IATA** is the International Air Transport Association. The **ARD** is the European Agreement Concerning the International Carriage of Dangerous Goods by Road and the **RID** are the International Regulations Concerning the Carriage of Dangerous Goods by Rail.

