

Page 1 of 7 CND-N-048

Prepared to OSHA	, ACC, ANSI and	WHMIS Standards
------------------	-----------------	-----------------

MSDS Revision Date 11/01/2002

	1. PRODUCT IDENTIFICATION				
1.1	Product Name:				
	SOLARSPEED SPRAY				
1.2	Chemical Name:				
1.3	Synonyms:				
1.4	Trade Names:				
1.5	Product Use:				
	COSMETIC USE ONLY				
1.6	Manufacturer's Name:				
	CREATIVE NAIL DESIGN, INC.				
1.7	Manufacturer's Address:				
	1125 JOSHUA WAY, VISTA, CA U.S.A., 92083				
1.8	Emergency Phone:				
	ROCKY MOUNTAIN POISON CONTROL CENTER: 1-303-623-5716				
1.9	Business Phone:				
	1-877-CND-NAIL (877-263-6245)				
	2. COMPOSITION & INGREDIENT INFORMATION				

		EXPOSURE LIMITS IN AIR					
		AC	GIH		OSHA		OTHER
CAS NO.	%	TLV ppm	STEL ppm	PEL ppm	STEL ppm	IDLH ppm	
107-46-0	< 78	0.3 mg/m ³	NE	0.3 mg/m ³	NE	NE	(C)
NA	10	NE	NE	NE	NE	NE	
NA	5	NE	NE	NE	NE	NE	
NA	<4	NE	NE	NE	NE	NE	
NA	2	NE	NE	NE	NE	NE	
	BALANCE	THE REMA	INING COM				IGNIFICANT
	107-46-0 NA NA	107-46-0 < 78 NA 10 NA 5 NA <4 NA 2	CAS NO. % TLV ppm 107-46-0 < 78	CAS NO. % ppm ppm 107-46-0 < 78	ACGIH CAS NO. % TLV ppm STEL ppm ppm PEL ppm ppm 107-46-0 < 78	ACGIH OSHA CAS NO. % TLV STEL PEL PEL STEL PPM PPM PPM PPM PPM PPM PPM PPM PPM PP	ACGIH OSHA TLV STEL ppm ppm ppm ppm ppm ppm ppm ppm ppm pp

NA = Not Available; ND = Not Determined; NE = Not Established; C = Ceiling Limit; See Section 16 for Additional Definitions of Terms Used NOTE: all WHMIS required information is included. It is located in appropriate sections based on the ANSI Z400.1-1998 format.



Page 2 of 7

CND-N-048

Pre	Prepared to OSHA, ACC, ANSI and WHMIS Standards					MSDS	MSDS Revision Date 11/01/2002		
			3. HAZAR	D IDENTI	FICATION				
3.1	3.1 Hazard Identification:								
3.2	Routes of Entry:		Inhalation:	YES	Absorption:	YES	Ingesti	ion:	YES
3.3	Effects of Exposure: Inhalation: Material may be irritating to mucous membranes. Ingestion: Material may be irritating to mucous membranes. Eyes & Skin: May cause eye irritation. May cause skin irritation.								
3.4	Symptoms of Overexposure: Redness, watering or swelling, if in eyes. Redness, irritation or itching on skin at site of contact.								
3.5									
3.6									
3.7	7 Target Organs: Eyes and skin.								
			4. FIRST	AID ME	ASURES				
4.1	Inhalation: If irritation occurs remove affected individual to fresh air. If breathing is difficult, give oxygen. If breathing stop perform artificial respiration at once. Seek immediate medical attention.								
	Eyes & Skin: In case of contact, immediately flush eyes with copious amounts of water for at least 15 minutes. Open and close eyelid(s) to ensure thorough irrigation. If irritation persists, consult a physician. In case of skin irritation, immediately wash skin with soap and copious amounts of water. Do not wear contaminated clothing until after it has been properly cleaned. If irritation persists, consult a physician.						mediately		
	Ingestion:	If swallowed, wash out m	outh with water. Co	all a physicio	an				
4.2	Medical Condition None known.	ns Aggravated by Exposure:				HEALTH			1
	None known.					FLAMMABILITY			2
						REACTIVITY 0			0
					·	PROTEC	TIVE EG	UIPMEN	Т



Page 3 of 7

CND-N-048

Prepared to OSHA, ACC, ANSI and WHMIS Standards MSDS Revision Date 11/01/2002 5. FIREFIGHTING MEASURES Flashpoint & Method: 120°F (calculated) 5.2 Autoignition Temperature: ND Flammability Limits: 5.3 Lower Explosive Limit (LEL): Upper Explosive Limit (UEL): Fire & Explosion Hazards: RED = FLAMMABILITY Flammable. BLUE = HEALTH YELLOW = REACTIVITY 5.5 Extinguishing Methods: WHITE = SPECIAL MEASURES CO₂, Halon, Dry Chemical, Foam, Water 0 0 = NO HAZARD 5.6 Firefighting Procedures 1 = MINIMAL HAZARD Wear self-contained breathing apparatus and protective clothing to prevent contact 2= SLIGHT HA7ARD 3 = MODERATE HAZARD with skin and eyes. Emits toxic fumes under fire conditions. Structural firefighters must 4 = SEVERE HAZARD wear SCBAs and full protective equipment. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product. 6. ACCIDENTAL RELEASE MEASURES Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., <1 gallon) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and

soap. Remove any contaminated clothing and wash thoroughly before reuse.

For spills ≥ 1 gallon, deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

7. HANDLING & STORAGE INFORMATION

Work & Hygiene Practices: 7.1

Use in a well-ventilated location (e.g., local exhaust ventilation, fans). Do not eat, drink or smoke while handling product.

7.2

Keep this material away from heat, sparks and open flame.

Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Store away from incompatible materials (see Section 10).

7.3 Special Precautions:

No special precautions.



11.4 Suspected Carcinogen:

MATERIAL SAFETY DATA SHEET

Page 4 of 7

CND-N-048

•	NAIL DESIGN®				
Prepared to OSHA, ACC, ANSI and WHMIS Standards			MSDS Revision Date 11/01/2002		
		3. EXPOSURE CONTROLS & PERSON	AL PROTECTION		
8.1		vantities (≥ 1 gallon) of product, provide adequate v lk or washbasin is available in case of exposure to e	ventilation (e.g., local exhaust ventilation, fans). Ensure		
8.2	authorized per U.S. OSHA's	•	handling. If necessary, use only respiratory protection U.S. state regulations, or the appropriate standards of		
8.3		required under normal conditions of use. Howevities (e.g., ≥ 1 gallon), safety glasses with side shield	ver, may cause irritation in some sensitive individuals. Is should be used.		
8.4	Hand Protection: None required under norma	al conditions of use. However, may cause skin irritatities (e.g., ≥ 1 gallon), wear rubber or plastic imperv	tion in some sensitive individuals.		
8.5	Body Protection: No apron required when ho When handling large quan	andling small quantities.	uge showers should be available. Upon completion of		
		9. PHYSICAL & CHEMICAL PR	OPERTIES		
9.1	Density:	0.8			
9.2	Boiling Point:	> 212°F			
9.3	Melting Point:	NA			
9.4	Evaporation Rate:	NA			
9.5	Vapor Pressure:	NA			
9.6	Molecular Weight:	NA NA			
9.7	Appearance & Color:	Clear liquid.			
9.8	Odor Threshold:	NA .			
9.9	Solubility:	Insoluble.			
9.10	рН	NA			
9.11	Viscosity:	NA NA			
9.12	Other Information:	NA NA			
		10. STABILITY & REACTIN	/ITY		
10.1	Stability:	Stable under ambient conditions.			
10.2	Hazardous Decomposition Products:	Oxides of carbon and nitrogen.			
10.3	Hazardous Polymerization:	Will not occur.			
10.4	Conditions to Avoid:	Exposure or contact with extreme temperature	es or incompatible materials.		
10.5	Incompatible Substances:	Strong oxidizers, acids and alkalis.			
		11. TOXICOLOGICAL INFOR	MATION		
11.1	Toxicity Data:	This product has not been tested on animals t	o obtain toxicological data. There are toxicology data e found in the scientific literature. These data have not		
11.2	Acute Toxicity:	See Section 3.3			
11.3	Chronic Toxicity:	See Section 3.6			
11.4	Suspected Carcinogen:	NE			



Page 5 of 7

CND-N-048

	WATE DESIGN					
Pre	pared to OSHA, ACC, A	ANSI and WHMIS Standards	MSDS Revision Date 11/01/200			
11.5	Reproductive Toxicity:	Name				
11.5	Mutagenicity:	None	and the state to be seen			
	-	This product is not reported to produce muta				
	Embryotoxicity:	This product is not reported to produce embr				
	Teratogenicity:	This product is not reported to cause teratogo				
Reproductive Toxicity: This product is not reported to cause reproductive effects in humans.						
11.6	Irritancy of Product:	See Section 3.3				
11.7	Biological Exposure Indices:	NE				
11.8	Physician Recommendations:	Treat symptomatically.				
		10 F00L00L0AL INFOR	MATION			
		12. ECOLOGICAL INFORM	MAIION			
12.1	Environmental Stability:	This product will slowly volatile from soil. O organic compounds.	Components of this product will slowly decompose in			
12.2	Effects on Plants & Animals:	There are no specific data available for this p	product.			
12.3	Effects on Aquatic Life:	There are no specific data available for this p	product.			
		13. DISPOSAL CONSIDER	ATIONS			
13.1	Waste Disposal:					
12.0	Special Considerations:	with all Federal, state, and local regulations.				
13.2	U.S. EPA WASTE NUMBER: D	001				
	U.S. LI'A WASIL NOMBER. D	301				
		14. TRANSPORTATION INFO	RMATION			
The	basic description (proper shi	pping name hazard class & division ID Number p	packing group) is shown for each mode of transportatio			
		n may be required by 49 CFR, IATA/ICAO, IMDG at				
14.1	49 CFR (GND):	, , , , , , , , , , , , , , , , , , , ,				
	NOT REGULATED BY THIS MO	DDE				
14.2	IATA (AIR):					
	CONSUMER COMMODITY,	7, ID8000				
14.3	IMDG (OCN):					
		(hexamethyldisiloxane), 3, UN1993, III, LTD QTY				
14.4	TDGR (Canadian GND):	QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QU	IANT ITÉE"			
	MAKK PACKAGE LIMITED (QUANTITY OF QUANTITE LIMITEE OF LID QIY OF QU	IANI LIEE			



310-360-3700 phone 310-360-5700 fax

http://www.shipmate.com/

MATERIAL SAFETY DATA SHEET

Page 6 of 7

CND-N-048

Prepared to OSHA, ACC, ANSI and WHMIS Standards MSDS Revision Date 11/01/2002 15. REGULATORY INFORMATION SARA Reporting Requirements: SARA Threshold Planning Quantity: 15.2 There are no specific Threshold Planning Quantities for the components of this product. 15.3 TSCA Inventory Status: The components of this product are listed on the TSCA Inventory. 15.4 CERCLA Reportable Quantity (RQ): 15.5 Other Federal Requirements: This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics). 15.6 This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. Class B2 Flammable Liquid. 15.7 State Regulatory Information: 16. OTHER INFORMATION Other Information: Flammable. Use only as directed. KEEP OUT OF REACH OF CHILDREN. Discontinue use immediately if irritation develops. Avoid eye contact. If eye contact occurs, flush with water. Do not ingest. If swallowed, do not induce vomiting; seek medical attention. See page 7 of this MSDS. 16.3 Disclaimer: This Material Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Creative Nail Design's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein related only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition. Prepared for: Creative Nail Design, Inc. 1125 Joshua Way Vista, CA 92083 1-877-CND-NAIL (877-263-6245) phone CREATIVE 760-599-4005 fax NAIL DESIGN http://www.creativenaildesign.com/ Prepared by: ShipMate, Inc. 18436 Hawthorne Boulevard, Suite 201 Torrance, CA 90504

Training & Consulting



Page 7 of 7

CND-N-048

Prepared to OSHA, ACC, ANSI and WHMIS Standards

MSDS Revision Date 11/01/2002

DEFINITIONS OF TERMS

A large number of abbreviations and acronyms appear on a MSDS. Some of these that are commonly used include the following:

CAS #: This is the Chemical Abstract Service Number that uniquely identifies each constituent.

EXPOSURE LIMITS IN AIR:

ACGIH - The American Conference on Governmental Industrial Hygienists, a professional association that establishes exposure limits.

TLV – Threshold Limit Value – an airborne concentration of a substance that represents conditions under which it is generally believed that all workers may be repeatedly exposed without adverse effect. The duration must be considered, including the 8-hour Time Weighted Average (TWA), the 15-minute Short Term Exposure Limit, and the instantaneous Ceiling Level (C). Skin absorption effect must also be considered.

OSHA – U.S. Occupational Safety and Health Administration

PEL – Permissible Exposure Limit – This exposure value means exactly the same as TLV, except that it is enforceable by OSHA. The OSHA Permissible Exposure Limits are based in the 1989 PELs and the June 1993 Air Contaminants Rule (<u>Federal Register</u>: 58: 35338-35351 and 58: 40191). Both the current PELs and the vacated PELs are indicated. The phrase "Vacated 1989 PEL," is placed next to the PEL which was vacated by Court Order.

IDLH – Immediately Dangerous to Life and Health – This level represents a concentration from which one can escape within 30-minutes without suffering escape-preventing or permanent injury. The **DFG** – **MAK** is the Republic of Germany's Maximum Exposure Level, similar to the U.S. PEL. NIOSH is the National Institute of Occupational Safety and Health, which is the research arm of the U.S. Occupational Safety and Health Administration (**OSHA**). NIOSH issues exposure guidelines called Recommended Exposure Levels (**RELs**). When no exposure guidelines are established; an entry of **NE** is made for reference.

FIRST AID MEASURES:

CPR: Cardiopulmonary resuscitation. Method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.

HAZARD RATINGS:

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: This rating system was developed by the National Paint and Coating Association and has been adopted by industry to identify the degree of chemical hazards. Health Hazard: 0 (minimal acute or chronic exposure hazard); 1 (slight acute or chronic exposure hazard); 2 (moderate acute or significant chronic exposure hazard); 3 (severe acute exposure hazard; onetime overexposure can result in permanent injury and may be fatal); 4 (extreme acute exposure hazard; onetime overexposure can be fatal). Flammability hazard: 0 (minimal hazard); 1 (materials that require substantial pre-heating before burning; 2 (combustible liquids or solids; liquids with a flashpoint of 38-93C [100-200F]); 3 (Class 1B and 1C flammable liquids with flash points below 38C [100F]; 4 (Class 1A flammable liquids with flash points below 23C [73F] and boiling points below 38C [100F]. Reactivity Hazard: 0 (normally stable); 1 (materials that can become unstable at elevated temperatures or which can react slightly with water); 2 (materials that are unstable but do not detonate when initiated or which can react violently with water); 3 (materials that can detonate when initiated or which can react explosively with water); 4 (materials that can detonate at normal temperatures or pressures). PPE Rating B: Hand and eye protection is required for routine chemical use.

NATIONAL FIRE PROTECTION ASSOCIATION: <u>Health Hazard</u>: 0 (material that on exposure under fire conditions would offer no hazard beyond that of ordinary combustible materials); 1 (materials that on exposure under fire conditions could cause irritation or minor residual injury); 2 (materials that on intense or continued exposure under fire conditions could cause temporary incapacitation or possible residual injury); 3 (materials that can on short exposure could cause serious temporary or residual injury); 4 (material that under very short exposure could cause death or major residual injury).

<u>Flammability Hazard and Reactivity Hazard</u>: Refer to definitions for "Hazardous Materials Identification System."

FLAMMABILITY LIMITS IN AIR:

Much of the information related to fire and explosion is derived from the National Fire Protection Association (NFPA). Flash Point – minimum temperature at which a liquid gives off sufficient vapors to form an ignitable mixture with air. Autoignition Temperature: The minimum temperature required to initiate combustion in air with no other source of ignition. LEL—the lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source. UEL—the highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source.

TOXICOLOGICAL INFORMATION:

Human and Animal Toxicology: Possible health hazards as derived from human data, animal studies, or from the results of studies with similar compounds are presented. Definitions of some terms use dint his section are: LD₅₀ – Lethal Dose (solids & liquids) which kills 50% of the exposed animals; LC50 – Lethal concentration (gases) which kills 50% of the exposed animals; ppm - concentration expressed in parts of material per million parts of air or water; mg/m³- concentration expressed in weight of substance per volume of air; mg/kg quantity of material, by weight, administered to a test subject, based on their body weight in kg. Other measures of toxicity include \mathbf{TD}_{lo} , the lowest dose to cause a symptom and **TCLo** the lowest concentration to cause a symptom; TD_{lo} , LD_{lo} , and LD_{o} , or TC, TC_{o} , LC_{lo} , and LC_{o} , the lowest dose (or concentration) to cause lethal or toxic effects. Cancer Information: The sources are: IARC - the International Agency for Research on Cancer; NTP - the National Toxicology Program, RTECS - the Registry of Toxic Effects of Chemical Substances, OSHA and CAL/OSHA. IARC and NTP rate chemicals on a scale of decreasing potential to cause human cancer with rankings from 1 to 4. Sub rankings (2A, 2B, etc.) are also used. Other Information: BEI - ACGIH Biological Exposure Indices, represent the levels of determinants which are most likely to be observed in specimens collected from a health worker who has been exposed to chemical to the same extent as a worker with inhalation exposure to the TLV. Ecological Information: EC is the effect concentration in water. BCF - Bioconcentration Factor, which is used to determine if a substance will concentrate in life forms that consume contaminated plant or animal matter. TL_m - median threshold limit; Coefficient of Oil/Water Distribution is represented by log Kow or log Koc and is used to assess a substance's behavior in the environment.

REGULATORY INFORMATION:

U.S. and CANADA: This section explains the impact of various laws and regulation of the material. **EPA** is the U.S. Environmental Protection Agency. **WHMIS** is the Canadian Workplace Hazardous Material Information System. **DOT** and **TC** are the U.S. Department of Transportation and Transport Canada, respectively. Superfund Amendments and Reauthorization Act (**SARA**); the Canadian Domestic/Non-Domestic Substance List (**DSL/NDSL**); the U.S. Toxic Substance Control Act (**TSCA**); Marine Pollutant status according to the DOT; the Comprehensive Environmental Response, Compensation, and Liability Act (**CERCLA or Superfund**); and various state regulations. This section also includes information on the precautionary warnings that appear on the material's package label.

EUROPEAN and INTERNATIONAL: EC is the European Community, formerly known as the EEC, European Economic Community). **EINECS:** This is the European Inventory of Now-Existing Chemical Substances. **AICS** is the Australian Inventory of Chemical Substances. **MITI** is the Japanese Minister of International Trade and Industry. **ECL** is the Korean Existing Chemicals List. **IMO** is the International Maritime Organization and **IATA** is the International Air Transport Association. The **ARD** is the European Agreement Concerning the International Carriage of Dangerous Goods by Road and the **RID** are the International Regulations Concerning the Carriage of Dangerous Goods by Rail.

